

Coupling Decoupling Network Accessories

30 mm calibration adapters

150 kHz – 230 MHz, N-Female to 1/2/3/4/5x 4mm banana plug shorting bar



Example: Calibration Adapter for CDN-M4

50 Ohm to 150 Ohm adapter

150 kHz – 230 MHz, 4W, N.Female / N-Male



1 Ordering Information

Part Number	Description
TBCDN-M1-AP	Adapter panel with shorting bar for M1 coupling decoupling network; N-Female to 4mm Banana plug
TBCDN-M2-AP	Adapter panel with shorting bar for M2 coupling decoupling network; N-Female to 2x 4mm Banana plug
TBCDN-M3-AP	Adapter panel with shorting bar for M3 coupling decoupling network; N-Female to 3x 4mm Banana plug
TBCDN-M4-AP	Adapter panel with shorting bar for M4 coupling decoupling network; N-Female to 4x 4mm Banana plug
TBCDN-M5-AP	Adapter panel with shorting bar for M5 coupling decoupling network; N-Female to 5x 4mm Banana plug
TBCDN-50-150	50 Ω to 150 Ω N-male to N-female adapter

2 History

Version	Date	Author	Changes
V1.0	24.3.2022	Mayerhofer	Creation of the document